**Degaussers Comparison Chart** 





TS-4XT IRONCLAD
Degausser with Erasure
Verification System



40,000 Gauss Degausser



TS-1XT IRONCLAD
Degausser with
Erasure
Verification System



TS-1XT NSA/EPL Listed Degausser



HD-3XTL IRONCLAD
Degausser with
Erasure
Verification System



HD-3XTL High-Volume Degausser



HD-2XT IRONCLAD
Degausser with Erasure
Verification System



HD-2XT High-Speed Degausser

| Specifications                                                                              | Verification System Degausser                                                                                                                                                                                                        | Erasure Degausser Verification System                                                                                                                                                                                                | Erasure Degausser Verification System                                                                                                                                                                                                  | Verification System Degausser                                                                                                                                                                                                        |  |
|---------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Certifications/Listings                                                                     | ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC                                                                                                                                                                                     | NSA/CSS • ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC                                                                                                                                                                           | UL·ETL·IEC·CSA·CE·RCM·TAA·FCC                                                                                                                                                                                                          | UL • ETL • IEC • CSA • CE • RCM • TAA • FCC                                                                                                                                                                                          |  |
| Verification<br>Options                                                                     | SCAN-1X standard • IRONCLAD optional                                                                                                                                                                                                 | SCAN-1X standard • IRONCLAD optional                                                                                                                                                                                                 | SCAN-1X standard • IRONCLAD optional                                                                                                                                                                                                   | IRONCLAD or SCAN-1X optional                                                                                                                                                                                                         |  |
| Magnetic Field                                                                              | 4 tesla (40,000 gauss) NOM                                                                                                                                                                                                           | 2 tesla (20,000 gauss) NOM                                                                                                                                                                                                           | 1 tesla (10,000 gauss) noм                                                                                                                                                                                                             | 1 tesla (10,000 gauss) nом                                                                                                                                                                                                           |  |
| Drawer/Slot<br>Capacity (HxWxD)                                                             | 1x 4 x 5.8 (in.)<br>25.4 x 101.6 x 147.3 (mm)                                                                                                                                                                                        | 1.25 x 4.3 x 5.9 (in.)<br>31.8 x 108 x 148.6 (mm)                                                                                                                                                                                    | 1.7 x 4.5 x 5.9 (in.)<br>43.2 x 114.3 x 148.6 (mm)                                                                                                                                                                                     | 1.25 x 4.3 x 5.9 (in.)<br>31.8 x 108 x 148.6 (mm)                                                                                                                                                                                    |  |
| Media Types                                                                                 | Hard drives: Laptop, standard, or network up to 1 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others                                                                                                      | Hard drives: Laptop, standard, or network up to 1.25 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others                                                                                                   | Hard drives:  Hard drives up to 1.7 in. in height including full height, standard and laptop drives  Tape media:  All LTO, all DLT, 3490, 9940,3592, AIT, and others                                                                   | Hard drives: Laptop, standard, network up to 1.25 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others                                                                                                      |  |
| Continuous Duty                                                                             | ✓                                                                                                                                                                                                                                    | ✓                                                                                                                                                                                                                                    | ✓                                                                                                                                                                                                                                      | ✓                                                                                                                                                                                                                                    |  |
| Degausser Throughput (hard drives per hour) Throughput with IRONCLAD (hard drives per hour) | Up to 480 (1.8 in.) Up to 360 (2.5 in.) Up to 80 (3.5 in.) Up to 80                                                                                                                                                                  | Up to 1,300 (1.8 in.)<br>Up to 875 (2.5 in.)<br>Up to 150 (3.5 in.)<br>Up to 120                                                                                                                                                     | Up to 4,500 (1.8 in.)<br>Up to 4,500 (2.5 in.)<br>Up to 450 (3.5 in.)<br>Up to 240                                                                                                                                                     | Up to 1920 (1.8 in.)<br>Up to 960 (2.5 in.)<br>Up to 240 (3.5 in.)<br>Up to 180                                                                                                                                                      |  |
| Charge Time                                                                                 | ~30 seconds                                                                                                                                                                                                                          | 15 seconds                                                                                                                                                                                                                           | 3 seconds                                                                                                                                                                                                                              | 8 seconds                                                                                                                                                                                                                            |  |
| Power                                                                                       | TS-4XT: 90-250VAC ±5%, 50/60 Hz<br>IRONCLAD: 90~240V 47-440 Hz                                                                                                                                                                       | TS-1XT: 90-250VAC ±5%, 50/60 Hz<br>IRONCLAD: 90~240V 47-440 Hz                                                                                                                                                                       | HD-3XTL: 90~250VAC ±5%, 50/60 Hz<br>IRONCLAD: 90~240V 47-440 Hz                                                                                                                                                                        | HD-2XT: 90-250VAC ±5%, 50/60 Hz<br>IRONCLAD: 90~240V 47-440 Hz                                                                                                                                                                       |  |
| Weight                                                                                      | TS-4XT: 130 lbs. (59 kg.)<br>Touchscreen: 4 lbs. (1.7 kg)                                                                                                                                                                            | TS-1XT: 105 lbs. (47.7 kg.)<br>Touchscreen: 4 lbs. (1.7 kg)                                                                                                                                                                          | HD-3XTL: 59 lbs. (27 kg.)<br>Touchscreen: 4 lbs. (1.7 kg)                                                                                                                                                                              | HD-2XT: 34 lbs. (15.4 kg.)<br>Touchscreen: 4 lbs. (1.7 kg)                                                                                                                                                                           |  |
| Size<br>(HxWxD)                                                                             | TS-4XT IRONCLAD: 19.3 x 9.8 x 29.1(in.) 490 x 247.7 x 740.2 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)                                                                                                              | TS-1XT IRONCLAD: 19.3 x 9.8 x 29.1(in.) 490 x 247.7 x 740.2 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)                                                                                                              | HD-3XTL IRONCLAD: 18.9 x 25.1 x 13 (in.) 480 x 637.5 x 328.9 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)                                                                                                               | HD-2XT IRONCLAD:<br>10.2 x 17.75 x 18.2 (in.)<br>260 x 451 x 463 (mm)<br>Touchscreen:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64 (mm)                                                                                                |  |
| Power Consumption                                                                           | Under standby: 108W While charging: 1272W (avg) At the time of erase: 120W IRONCLAD: 15W                                                                                                                                             | Under standby: 108W While charging: 1272W (avg) At the time of erase: 120W IRONCLAD: 15W                                                                                                                                             | Under standby: 36W While charging: 300W (avg) At the time of erase: 36W IRONCLAD: 25W                                                                                                                                                  | Under standby: 17W While charging: 145W (avg) At the time of erase: 17W IRONCLAD: 15W                                                                                                                                                |  |
| Capacitive Discharge                                                                        | ✓                                                                                                                                                                                                                                    | ✓                                                                                                                                                                                                                                    | ✓                                                                                                                                                                                                                                      | ✓                                                                                                                                                                                                                                    |  |
| Warranty                                                                                    | TS-4XT: One-year manufacturer's limited warranty standard, optional three year limited warranty TS-4XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard | TS-1XT: One-year manufacturer's limited warranty standard, optional three year limited warranty TS-1XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard | HD-3XTL: One-year manufacturer's limited warranty standard, optional three year limited warranty HD-3XTLA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard | HD-2XT: One-year manufacturer's limited warranty standard, optional three year limited warranty HD-2XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard |  |











PD-5 Hard Drive Destroyer



SSD-1 Solid-State Destroyer (for use with the PD-5)



FLASHPRO IRONCLAD Solid-State Shredder with Destruction Verification



FLASHPRO Solid-State Shredder

| Specifications                                  | Hard Drive Destroyer with Hard Drive Destroyer  Destruction Verification                                                                                                                                                         | (for use with the PD-5)                                                      | Destruction Verification Solid-State Shredder                                                                                |  |  |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|--|--|
| Certifications/Listings                         | NSA/CSS • ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC                                                                                                                                                                       | TAA • Patented                                                               | CE • Meets E-3 Security Requirements • TAA                                                                                   |  |  |
| Verification Options                            | IRONCLAD or SCAN-1X options                                                                                                                                                                                                      | IRONCLAD and SCAN-1X capable                                                 | IRONCLAD optional                                                                                                            |  |  |
| Destruction Chamber<br>Capacity (HxWxD)         | 2.26 x 4.9 x 6.8 (in.)<br>57.4 x 123.7 x 172.2 (mm)                                                                                                                                                                              | 0.5 x 3 x 6 (in.)<br>13.2 x 73.7 x 152.4 (mm)                                | 6.5 in. (165 mm)                                                                                                             |  |  |
| Media Types                                     | Laptop, standard, or network hard drives up to 2.25 in. in height <sup>1</sup>                                                                                                                                                   | SSD, flash drives, USB thumb drives, mobile phones², SSHD controller boards¹ | Mobile phones², mini-tablets (up to 6.5 in. or 165 mm in width)², solid-state drives (St USB thumb drives, and optical media |  |  |
| Throughput<br>(hard drives per hour)            | Up to 1,800 (2.5 in.)<br>Up to 360 (3.5 in.)                                                                                                                                                                                     | 180-720 pieces per hour (depending on size of media)                         | 100 Mobile phones** 500 SSD drives* 500 USB thumb drives 500 CDs\DVDs                                                        |  |  |
| Throughput With IRONCLAD (hard drives per hour) | Up to 180 (hard drives per hour)                                                                                                                                                                                                 | •                                                                            | Up to 180 pieces of media                                                                                                    |  |  |
| Cycle Time                                      | 20 seconds                                                                                                                                                                                                                       | 20 seconds                                                                   | Depends on media size                                                                                                        |  |  |
| Crush Force                                     | 10+ tons                                                                                                                                                                                                                         | 90 spikes                                                                    | •                                                                                                                            |  |  |
| Shred Size                                      | •                                                                                                                                                                                                                                | •                                                                            | 0.16 x 0.6 in. (4 x 15 mm)                                                                                                   |  |  |
| Weight                                          | 79 lbs. (35.9 kg.) • Touchscreen: 4lbs. (17 kg.)                                                                                                                                                                                 | 8.3 lbs. (3.8 kg.)                                                           | 256 lb (116 kg)                                                                                                              |  |  |
| Size (HxWxD)                                    | 14.9 x 7.5 x 18.6 (in.)<br>377.7 x 190.8 x 473.5 (mm)                                                                                                                                                                            | 2.8 x 4.8 x 6.8 (in.)<br>71.1 x 121.9 x 173.4 (mm)                           | 39 x 22.8 x 24 (in.)<br>990.6 x 579.1 x 609.6 (mm)                                                                           |  |  |
| Power                                           | PD-5: 100-240VAC ±5%, 50/60 Hz<br>IRONCLAD: 90~240V 47-440 Hz                                                                                                                                                                    |                                                                              | 120 V/60 Hz, 230 V/50 Hz, 240 V/50 Hz*<br>(Plugs into 20A receptacle)<br>IRONCLAD: 90~240V 47-440 Hz                         |  |  |
| Power Consumption                               | During standby: 90W During crush: 1200W (max)                                                                                                                                                                                    | •                                                                            | During standby: 8.4W Running no load: 960W (max) Running with load: 1450W avg. / 2400W max.                                  |  |  |
| Accessories Included                            | •                                                                                                                                                                                                                                | 5 SSD-MT media transport sleeves for destroying solid-state media            | Catch basket Plastic bag Oil bottle                                                                                          |  |  |
| Warranty                                        | PD-5: One-year manufacturer's limited warranty standard, optional three year limited warranty PD-5A/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard | SSD-1 • SSD-1A/E: Ninety-day manufacturer's limited warranty standard        | FLASHPRO • FLASHPRO-A/E: One-year manufacturer's limited warranty standard                                                   |  |  |

<sup>&</sup>lt;sup>1</sup> Enterprise SSDs must have rack mounts and casings removed prior to destruction

<sup>&</sup>lt;sup>2</sup> All items must have the battery removed prior to destruction

















IC-TS1XT
Erasure Verification
Specifications System

IC-HD3XTL Erasure Verification System

IC-HD2X Erasure Verification System

IC-SSC25SSD Erasure Verification System

IC-PD5
Destruction Verification
System

IC-FLASHPRO
Destruction Verification
System

IC-UNIVERSAL
Destruction Verification Me
System R

Media Destruction Report Package

| Specifications              | System                                                                                                                                          | System                                                                                                                                           | System                                                                                                                                          | System                                                                                                                                          | System                                                                                                                                          | System                                                                                                                                          | System                                                                                                                                          | Report Package                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Certifications/<br>Listings | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                        | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                         | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                        | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                        | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                        | CE • Security Level DIN<br>66399 O-3 / T-4 / E-3 • TAA                                                                                          | UL • ETL • IEC • CSA •<br>CE • FCC • TAA                                                                                                        | N/A                                                                      |
| To be used with             | TS-4XT 40,000 Gauss<br>degausser<br>TS-1XT NSA-listed<br>degausser                                                                              | HD-3XTL high-volume degausser                                                                                                                    | HD-2XT high-speed degausser                                                                                                                     | SPACESAVER<br>Compliance Package                                                                                                                | PD-5 physical destroyer                                                                                                                         | FLASHPRO                                                                                                                                        | UNIVERSAL application                                                                                                                           | TS-1XT • TS-1XT •<br>HD-3XTL • HD-2XT<br>• HD-2XTSS • PD-5               |
| Includes                    | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head,     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | IRONCLAD software to generate Certificate of Erasure and Destruction     Touch screen control head     Image capture device     Barcode scanner | Media destruction<br>report software     Barcode scanner                 |
| Hardware<br>Needed          | •                                                                                                                                               | •                                                                                                                                                | •                                                                                                                                               | •                                                                                                                                               | •                                                                                                                                               | •                                                                                                                                               | •                                                                                                                                               | Laptop, desktop computer, or tablet                                      |
| Storage<br>Capacity         | 16GB                                                                                                                                            | 16GB                                                                                                                                             | 16GB                                                                                                                                            | 16GB                                                                                                                                            | 16GB                                                                                                                                            | 16GB                                                                                                                                            | 16GB                                                                                                                                            | •                                                                        |
| Weight                      | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>1.2 lbs (.5 kg)                                                                              | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>9.5 lbs (4.3 kg)                                                                              | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>1.1 lbs (.5 kg)                                                                              | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>1.1 lbs (.5 kg)                                                                              | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>1.1 lbs (.5 kg)                                                                              | Control Head:<br>4 lbs (1.7 kg)<br>Camera Unit:<br>1.1 lbs (.5 kg)                                                                              | Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)                                                                                       | 1.6 lbs. (.73 kg)                                                        |
| Size<br>(HxWxD)             | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>7.7 x 7.8 x 5 (in.)<br>197 x 198 x 127 (mm)                     | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>14.5 x 11.9 x 6.4 (in.)<br>369 x 303 x 163 (mm)                  | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>9 x 5.5 x 5.8 (in.)<br>229 x 140 x 146 (mm)                     | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>9 x 5.5 x 5.8 (in.)<br>229 x 140 x 146 (mm)                     | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>8.2 x 5.7 x 5.6 (in.)<br>208 x 146 x 142 (mm)                   | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>8.2 x 5.7 x 5.6 (in.)<br>208 x 146 x 142 (mm)                   | Control Head:<br>6.6 x 9.6 x 2.5 (in.)<br>168 x 244 x 64(mm)<br>Camera Unit:<br>8.2 x 5.7 x 5.6 (in.)<br>208 x 146 x 142 (mm)                   | 8.7 X 6.5 X 3.4 (in.)<br>221 x 165 x 86.4<br>(mm)                        |
| Power<br>Requirements       | 90-240VAC, 47-440 Hz                                                                                                                            | 90-240VAC, 47-440 Hz                                                                                                                             | 90-240VAC, 47-440 Hz                                                                                                                            | 90-240VAC, 47-440 Hz                                                                                                                            | 90-240VAC, 47-440 Hz                                                                                                                            | 90-240VAC, 47-440 Hz                                                                                                                            | 90-240VAC, 47-440 Hz                                                                                                                            | •                                                                        |
| Power<br>Consumption        | 15W                                                                                                                                             | 25W                                                                                                                                              | 15W                                                                                                                                             | 15W                                                                                                                                             | 15W                                                                                                                                             | 15W                                                                                                                                             | 15W                                                                                                                                             | •                                                                        |
| Warranty                    | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                        | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard                       | Scanner:<br>Ninety-day<br>manufacturer's<br>limited warranty<br>standard |















RCC

DDR Degauss, Destroy, Recycle

DD

SSC-25SSD

| Specifications                              | Enclosed Destruction Cart                                                                                                                                                                                                          | Data Eliminator Cart                                                                                                                                                                                                                              | Workstations                                                                                                                                                                                        | Degauss, Destroy, Mobility                                                                                                                                                                                                                                                  | Degauss, Destroy                                                                                                                                                                     | SPACESAVER                                                                                                                                                                             |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Degausser<br>Options  Destroyers<br>Options | TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser  PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer                                                                                                                       | TS-4XT 40,000 Gauss degausser<br>TS-1XT NSA Listed degausser<br>HD-3XTL high-volume degausser<br>HD-2XT high-speed degausser<br>PD-5 NSA Listed HDD destroyer<br>SSD-1 SSD destroyer                                                              | TS-4XT 40,000 Gauss degausser<br>TS-1XT NSA Listed degausser<br>HD-3XTL high-volume degausser<br>HD-2XT high-speed degausser<br>PD-5 NSA Listed HDD destroyer<br>SSD-1 SSD destroyer                | TS-4XT 40,000 Gauss degausser<br>TS-1XT NSA Listed degausser<br>HD-3XTL high-volume degausser<br>HD-2XT high-speed degausser<br>PD-5 NSA Listed HDD destroyer<br>SSD-1 SSD destroyer                                                                                        | TS-4XT 40,000 Gauss degausser<br>TS-1XT NSA Listed degausser<br>HD-3XTL high-volume degausser<br>HD-2XT high-speed degausser<br>PD-5 NSA Listed HDD destroyer<br>SSD-1 SSD destroyer | HD-2XTSS high-speed<br>degausser<br>(Same specifications as<br>HD-2XT)<br>PD-5 NSA Listed HDD<br>destroyer                                                                             |
| Verification<br>Options                     | IRONCLAD optional<br>SCAN-1X standard                                                                                                                                                                                              | IRONCLAD optional<br>SCAN-1X standard<br>(opional with HD-2XT packages)                                                                                                                                                                           | IRONCLAD optional<br>SCAN-1X optional<br>(opional with HD-2XT packages)                                                                                                                             | IRONCLAD optional<br>SCAN-1X optional<br>(opional with HD-2XT packages)                                                                                                                                                                                                     | IRONCLAD optional<br>SCAN-1X optional<br>(opional with HD-2XT packages)                                                                                                              | SSD-1 SSD destroyer  IRONCLAD optional SCAN-1X standard                                                                                                                                |
| Platform                                    | CART-ICC Mobile Destruction Cart                                                                                                                                                                                                   | CART-RCCR Data Eliminator Cart                                                                                                                                                                                                                    | SW-2 workstation table and bins                                                                                                                                                                     | Transport Case                                                                                                                                                                                                                                                              | •                                                                                                                                                                                    | SSD-CADDY destruction accessory station                                                                                                                                                |
| Features &<br>Benefits                      | Take destruction to the media Maintains chain-of-custody Eliminates risk of physical data breach Removable doors Large wheels provide effortless maneuvering Superior turning capabilities Provides power for additional equipment | Take destruction to the media Maintains chain-of-custody Eliminates risk of physical data breach Agile and safe mobile operations Superior turning capabilities Provides power for additional equipment Strong, lightweight aluminum construction | Custom designed table Locking storage compartment Includes one large shatter resistant recycling bin Includes red media bin for media awaiting degaussing and yellow media bin for after degaussing | Die-cut foam to protect equipment during transit     High-quality ball bearings, smooth-rolling wheels     Full-swivel, locking, and removable casters     Recessed handles     Recessed latches for secure transport     Fits through standard doorways and into elevators | Complete data erasure in seconds     Physical destruction provides visual evidence media has been sanitized                                                                          | Regulatory compliance in a small footprint     Exclusive vertical HD-2XTSS     Includes patented SSD-1 solid-state destroyer     SCAN-1X Media Destruction Report software and scanner |
| Power                                       | CART-EDC: Shore power                                                                                                                                                                                                              | CART-RCC: Shore power                                                                                                                                                                                                                             | SW-2 Table: N/A                                                                                                                                                                                     | Cases: N/A                                                                                                                                                                                                                                                                  | See individual product descriptions                                                                                                                                                  | See individual product descriptions                                                                                                                                                    |
| Weight                                      | CART-EDC: 490 lbs. (222.3 kg) fully equipped*                                                                                                                                                                                      | <b>CART-RCC:</b> 71 lbs. (32.2 kg)                                                                                                                                                                                                                | <b>SW-2 Table:</b> 195 lbs. (88.45 kg)                                                                                                                                                              | Cases: weight varies depending on package                                                                                                                                                                                                                                   | See individual product descriptions                                                                                                                                                  | See individual product descriptions                                                                                                                                                    |
| Size                                        | CART-EDC: 42.7 x 30.4 x 36.4<br>(in.) 1085.8 x 772 X 924.4(mm)<br>Height w/IRONCLAD option 53.8<br>in. (1365.3 mm)*<br>Depth with handle 39.09 in.<br>(992.9 mm)                                                                   | CART-RCC: 42 x 24 x 43 (in.) / 106.68 x 60.96 x 109.22 (cm)                                                                                                                                                                                       | <b>SW-2 Table:</b> 36 x 50 x 28 in.<br>914.4 x 1270 x 711.2 mm.                                                                                                                                     | Cases: weight varies depending on package                                                                                                                                                                                                                                   | See individual product descriptions                                                                                                                                                  | See individual product descriptions                                                                                                                                                    |
| Warranty                                    | CART-ICC:<br>One-year parts and labor                                                                                                                                                                                              | CART-RCCR:<br>One-year parts and labor                                                                                                                                                                                                            | SW-2 table:<br>One-year parts and labor                                                                                                                                                             | CASES:<br>Ninety-day limited warranty<br>standard                                                                                                                                                                                                                           | See individual product descriptions                                                                                                                                                  | See individual product descriptions                                                                                                                                                    |

For components, please see individual product warranty descriptions
\* Specifications may vary depending on part number ordered. Contact your account manager for specifications.